TECHNICALDATASHEET

THERMOSTATIC POWER SHOWER 1500

ProductSpecification

Product Code: HY POWSHX MC / HY POWSHX W

Finish: Matt Chrome / White

Product Type: Contemporary

Operation: Push button start/stop

(single rotary dial for temperature adjustment)

Power ratings: 230v AC@50Hz/3Amp/150W

Constructions: Plastic (ABS) casing

Supply: Low pressure gravity systems only


Inlet Connections: 15mm push-fit

Outlet Connection: G 1/2"

Water Pressure: Min. 0.1 bar, Max. 1.0 bar

BRISTAN





AdditionalInformation

- · Eco button for deactivation of boost.
- 15 minute motor rating (unit will need to cool down if thermal cut out trips).
- Thermostatic shower with built in electric pump drawing water from gravity supplies.
- Thermostatic cartridge maintains showering temperature to +/- 1°C by compensating for changes in the incoming water temperature and pressure providing a stable outlet temperature.
- Automatic shut off in the event of hot or cold water supply failure, thus reducing the risk of injury.
- On/off operated by push button allowing temperature setting to remain the same after each use.
- Pipe access is from the right side, fed from either top, bottom or rear of the unit and the fitting are push-fit.
- Supplied with 1.5m hose, adjustable riser kit and 3 mode handset with rub clean nozzles. The riser rail
 has a built in soap tray, integral hose retainer and spirit level to assist in fitting and as it fits flush against the wall
 any previous fixing holes can be concealed.
- Under no circumstances should the power shower be connected to mains water supply.

Technical Advice: For further information please call 0844 7016273 or email customercare@bristan.com.

Guarantee: 2 years covering manufacturing faults.

Compliance/Approvals

WRAS

BEAB EMC: Certificate No. EE0084

BEAB Safety CE Mark

FlowRates (litres per minute)

System Pressure	Open Outlet (eco mode)
HY POWSHX MC/W	10.0





